

# Precision Balance g/m<sup>2</sup>

Precision balance, solid, lightweight and accurate, can be used for many weighing tasks, and can display, besides the standard units like grams, also directly in g/m<sup>2</sup> and oz/yd<sup>2</sup>.



- Modern and attractive design
- Backlit digital display
- Counting function
- Percent function
- Auto tare and auto zero functions
- Weighing units: g, oz, ct, lbs, %, pcs, tex, g/m<sup>2</sup>, oz/yd<sup>2</sup>
- Includes adaptor, optional internal rechargeable battery
- RS-232 data output
- Low battery indicator

## Features

- Displays directly in g/m<sup>2</sup>
- Rugged design for long life operation

## Technical details

Capacity	200 g (20000 g/m <sup>2</sup> )
Resolution	0.01 g (1 g/m <sup>2</sup> )
Tare range	0 - 200 g
Dim. plate	115 mm ø
Dim. balance	29 x 22 x 14 cm
Power	Adaptor 230 V
Nett weight	0.6 kg

## Standards

EN 536 · EN 12127 · EN ISO 2286-2 · ISO 3801 · DIN 53104 · DIN 53854 · TAPPI T410 · SCAN P6 · M&S P65 · NP 1701 · ASTM D3776 · ASTM D2646 · BS 2471 · BS 3424 · NF G07 115 · NF G07 150 · EDANA 40.2 · INDA 130.0 · IWSTM 13 · UNI 5114 · UNE 40339 · FINAT 12 · FEFCO 2 · FEFCO 6 · FEFCO 10 · NEN 1109